



Main

Range of product	Altivar
Product or component type	Communication module

Complementary

Range compatibility	Altivar 32 Altivar Process Modular Altivar Easy 610 Altivar Process ATV900 Altivar Machine ATV340 Altivar Machine ATV320 Altivar Process ATV600 Lexium 32
Communication port protocol	Profibus DP V1
Electrical connection	1 female connector SUB-D 9
Transmission rate	9.6 kbps...12 Mbps
Addressing	1...126 configurable by graphic terminal/SoMove software Configuration settings
Communication service	4 configurable telegrams Mapping of the process data from the master Parameters management compliant with PROFIdrive V4.1 Several DP V1 messaging modes Drive profile native ATV32 conforming to IEC 61800-7-201 (CiA 402)
Display type	1 LED RUN 1 LED bus fault (BF)
Alarm function	Diagnostic data with VSD status Standard identification and maintenance requests Host drive handled from two masters (MS0 and MS1)
Bus profile	CiA 402 PROFIdrive

Environment

Standards	IEC 61800-7-201 (CiA 402)
-----------	---------------------------

Offer Sustainability

RoHS (date code: YYWW)	Compliant - since 0936 - Schneider Electric declaration of conformity
------------------------	---

Contractual warranty

Warranty period	18 months
-----------------	-----------
