



## Main

Range	Acti 9
Product name	Acti 9 MIN
Device short name	MINs
Product or component type	Silent electronic timer
Product compatibility	Mechanical compatibility with electrical comb busbars
Colour tint	White (RAL 9003)

## Complementary

Device application	Building
Load type	230 V AC halogen lamp, ( 2300 W ) 230 V AC incandescent lamp, ( 2300 W ) 7 fluorescent lamp, balast : electronic, ( 11 W ) 7 fluorescent lamp, balast : electronic, ( 15 W ) 7 fluorescent lamp, balast : electronic, ( 20 W ) 7 fluorescent lamp, balast : electronic, ( 23 W ) 9 fluorescent lamp, balast : electronic, ( 7 W ) Dual mounted fluorescent tube, balast : conventional, ( 2300 VA ) Fluocompact lamp, balast : conventional, ( 1500 VA ) Fluorescent tube, balast : electronic, ( 300 VA ) Non-corrected fluorescent tube, balast : conventional, ( 2300 VA ) Parallel-corrected fluorescent tube, balast : conventional, ( 400 VA ) Serial-corrected fluorescent tube, balast : conventional, ( 2300 VA )
Power consumption in VA	<= 6 VA
Maximum switching current	16 A - 230 V AC pf = 1
[Ue] rated operational voltage	230 V ( +10 % -15 % ) AC 50/60 Hz
Time delay	Adjustable from 0.5 to 20 minutes
Mounting support	DIN rail
9 mm pitches	2
Connections - terminals	Screw terminals
Electrical insulation class	Class II
Width	18 mm

Height	89 mm
Depth	66 mm
Product weight	75 g

## Environment

Ambient air temperature for operation	-10...50 °C
IP degree of protection	IP20 B

## Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0946 - Schneider Electric declaration of conformity <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold <a href="#">Reference not containing SVHC above the threshold</a>
Product environmental profile	Available
Product end of life instructions	Available

## Contractual warranty

Warranty period	18 months
-----------------	-----------